



22-25HP Series Tractor Specifications and Quotation List



Main Features:

- ▲ Specially used in mountain areas and muddy roads;
- ▲ It has the characteristics of high transmission efficiency, low tremble, high traction, high adaptability and easy start;
- ▲ Jaw type differential lock can improve the pass-ability;
- ▲ Hydraulic output interface can make direct connection with the dump trailer;
- ▲ This series of tractor can have many different configurations according to customer's demands.

Main Technical Parameters:				
Model	BN-224	BN-220	BN-254	BN-250
Type	4WD	2WD	4WD	2WD
Dimensions(L×W×H)	2854×1696×1414			
Tread	front wheel 1000; rear wheel 1300			
Wheel base	1598	1559	1598	1559
Min. Ground Base	266	330	266	330
Dry Mass (kg)	1130	1060	1130	1060
Engine	Vertical, 2-cylinder, Water Cooled and 4-stroke			
Rated Power (kw)	16.1	16.1	18.4	18.4
Rated Rev. (r/min)	2400/2500			
Front tire	6.00-16	4.00-16	6.00-16	4.00-16



Zhengzhou Bona Enterprise Co., Ltd

<http://www.bona-farmmachine.com>

Rear tire	9.50-24	9.50-24	9.50-24	9.50-24
Clutch	Dry-friction, Single Stage or Two Stage			
Steering	Mechanical Type or Hydraulic Type			
Gearbox	6+2 or 8+2			
Suspension Type	Catalogue O or I			
PTO Shaft	540/1000rpm or 540/720rpm			