



160HP Farm Tractor Specifications and Quotation List



The tractor BN-X1604, 160HP, 4WD is developed on the basis of the Italian wheeled tractor chassis technology, adopting the British technology-based 6-cylinder turbocharged engine, which is featured with low specific fuel consumption and better power economic efficiency. The tractor has multiple gears, a wide speed range, and a large capacity of fuel tank, ensuring long-time operations with a single fueling. Besides, it is flexible in steering and easy to operate.

Main Features:

- ▲ 4 in1 combined light is used in the front, and modular lights can provide good lighting at night;
- ▲ It has the characteristics of high transmission efficiency, low tremble, high traction, high adaptability and easy start;
- ▲ Hydraulic output interface can make direct connection with the dump trailer, mower, backhoe, plough, etc;
- ▲ This series of tractor can have many different configurations according to customer's demands.

Main Technical Parameters:	
Model	BN-X1604
Tractor	
Type	4x4
Overall Dimensions (L×W×H) (mm)	5285x2696x2945
Wheelbase (mm)	2848
Min. Ground Clearance (mm)	459
Min. Operating Mass (kg)	6740
Tire Spec. Front / Rear	14.9-28 / 18.4-38
Wheel tread, Front / Rear	1680-2176 / 1620-2200
Gear shift, Forward / Backward	12 / 4



Speed range (Km/h), Forward / Backward	2.25-29.06 / 4.25-11.47
PTO Power (Kw)	106
Lifting Force(KN)	36
Diesel Engine	
Model	SC8D190.1G2
Type	Six cylinder, vertical, water cooled, four stroke, direct injection, turbocharged
Displacement (L)	8.27
Rated Power / Speed (Kw) / (r/min)	117.6 / 2200

Structure and specification are subject to change without notice.