



BONA 18-20HP Series Tractor Specifications and Quotation List



Main Features:

- ▲ Specially used in mountain areas and muddy roads;
- ▲ It has the characteristics of high transmission efficiency, low tremble, high traction, high adaptability and easy start;
- ▲ Jaw type differential lock can improve the pass-ability;
- ▲ Hydraulic output interface can make direct connection with the dump trailer;
- ▲ This series of tractor can have many different configurations according to customer's demands.



Main Technical Parameters:				
Model	BN-184	BN-180	BN-204	BN-200
Type	4WD	2WD	4WD	2WD
Dimensions(L×W×H)(mm)	2854×1696×1414			
Tread (mm)	front wheel 1000; rear wheel 1300			
Wheel base (mm)	1598	1559	1598	1559
Min. Ground Base (mm)	266	330	266	330
Dry Mass (kg)	1100	1040	1100	1040
Engine	Vertical, 2-cylinder, Water Cooled and 4-stroke			
Rated Power (kw)	13.2	13.2	14.72	14.72
Rated Rev. (r/min)	2200/2300			
Front tire	6.00-12	4.00-16	6.00-12	4.00-16
Rear tire	8.30-24	8.30-24	8.30-24	8.30-24
Clutch	Dry-friction, Single Stage or Two Stage			
Steering	Mechanical Type or Hydraulic Type			
Gearbox	6+2 or 8+2			
Suspension Type	Catalogue O			
PTO Shaft	540/1000rpm or 540/720rpm			