



BONA 70-75HP Series Tractor Specifications and Quotation List



Main Features:

- ▲ Specially used in mountain areas and muddy roads;
- ▲ 4 in1 combined light is used in the front, and modular lights can provide good lighting at night;
- ▲ It has the characteristics of high transmission efficiency, low tremble, high traction, high adaptability and easy start;
- ▲ Hydraulic output interface can make direct connection with the dump trailer, mower, backhoe, plough, etc;
- ▲ This series of tractor can have many different configurations according to customer's demands.

Main Technical Parameters:				
Model	BN700	BN704	BN750	BN754
Driving	4x2	4x4	4x2	4x4
Dimensions(L×W×H)(mm)	4010x1929x2568			
Tread for front wheel(mm)	1500	1450	1500	1450
Tread for rear wheel(mm)	1530	1530	1530	1530
Wheel base(mm)	2188	2236	2188	2236
Min. Ground Base(mm)	430	340	430	340
Engine	Vertical, direct injection, water cooled, 4 cylinder, 4 stroke			
Rated Power (kw)	51.5	51.5	55.2	55.2



Rated Rev. (r/min)	2200			
Front Tire	6.5-20	8.3-24	6.5-20	8.3-24
Rear Tire	14.9-30			
Clutch	Dry, Dual-stage type			
Steering	Hydraulic steering			
Gearbox	8F+2R			
Category of 3-point link	Rear, Category II			
PTO Shaft	760/1000			
Hydraulic output valve	one or two way valve			
Lifting capacity(KN)	12.5	12.5	13	13