



BONA 80-85HP Series Tractor Specifications and Quotation List



Main Features:

- ▲ Specially used in mountain areas and muddy roads;
- ▲ It is adopted Chinese famous brand engine, which has a big rated power, low noise, low emissions, environmental protection and energy saving;
- ▲ It has the characteristics of high transmission efficiency, low tremble, high traction, high adaptability and easy start;
- ▲ Hydraulic output interface can make direct connection with the dump trailer, mower, backhoe, plough, etc;
- ▲ This series of tractor can have many different configurations according to customer's demands.

Main Technical Parameters:				
Model	BN800	BN804	BN850	BN854
Driving	4x2	4x4	4x2	4x4
Dimensions(L×W×H)(mm)	3700x2050x2700			
Tread for front wheel(mm)	1485	1610	1485	1610
Tread for rear wheel(mm)	1620-2020(usual 1620)			
Wheel base(mm)	2362	2195	2362	2195
Min. Ground Base(mm)	476	379	476	379
Engine	Vertical, direct injection, water cooled, 4 cylinder, 4 stroke			



Zhengzhou Bona Enterprise Co., Ltd

<http://www.bona-farmmachine.com>

Rated Power (kw)	58.8	58.8	62.5	62.5
Rated Rev. (r/min)	2300			
Front Tyre	6.5-20/7.5-16	11.2-24	6.5-20/7.5-16	11.2-24
Rear Tyre	16.9-34			
Clutch	Dry, Dual-stage type			
Steering	Hydraulic steering			
Gearbox	8F+2R			
Category of 3-point link	Rear, Category II			
PTO Shaft	760/1000			
Hydraulic output valve	one or two way valve			
Lifting capacity(KN)	>15	>16	>15	>16