



1. High oil yielding, low oil residual in the cake: The oil left in cake is less than 6%. The cake thickness can be adjusted once the machine stops running;
2. Compact size: only 10-20m² is enough.
3. High purity: machine surface is made of chrome plated stainless steel, in line with food hygiene standards.
4. Easy operation. You should operate as per the instruction.
5. Components: Screw pressing part, Electrical controlling system, automatic heater, adjusting mechanism, driving unit and vacuum oil filter etc.
6. Multi-functional: used for pressing soybean, sunflower seeds, peanut, sesame, rapeseeds, flax seed, camellia, cotton seed, cashew, hemp seed, linseeds, coconut(copra), palm, palm kernel, pumpkin seeds, and walnuts and all the oil crops.

Screw Oil Press 1

Model	6YL-165
-------	---------

Capacity	500kg
Power	22kw
Weight	1500kg
Size	2290x750x1020 (mm)
Residue oil rate	<6%

Model	6YL-130
Capacity	450kg/h
Power	15kw
Weight	730kg
Size	2240x610x815 (mm)
Residue oil rate	<6%

Model	6YL-120
Capacity	350kg/h
Power	15kw
Weight	600kg
Size	2100x610x785 (mm)
Residue oil rate	<6%

D—1685

Name Model		D-1685
Diameter of Squeezing Bolt		80mm
Speed of Squeezing Bolt		60r/min
Diameter of Internal Circle of Pressing Chest		82mm
Configuration Power	Main Engine	6-5.5kw
	Heater	3kw
Handling Capacity		80-160kg/h
Weight of Complete Machine		780kg
Size (LxWxH) (mm)		1700x1300x1600

D—1688

Name Model		D-1688
Diameter of Squeezing Bolt		100mm
Speed of Squeezing Bolt		40r/min
Diameter of Internal Circle of Pressing Chest		102mm
Configuration Power	Main Engine	6-7.5kw
	Heater	3.5kw
Handling Capacity		150-250kg/h
Weight of Complete Machine		1100kg
Size (LxWxH) (mm)		1980x1450x1800

Zhengzhou Bona Enterprise Co., Ltd

<http://www.bona-farmmachine.com>

E-mail: zzbona@zzbona.com