

**10-20HP Series Walking Tractor Specifications and Quotation List**

High transmission efficiency, low tremble, high traction, high adaptability and easy start. Multifunctional, well designed and well made.

Main Technical Parameters:						
Model		BN101C	BN111	BN121	BN151-1	BN191
Overall Dimensions(L×W×H)(mm)		2200×960×1120	2260×930×1120	2360×1100×1090	2420×1600×1230	2490×1600×1265
Wheelbase(mm)		735-795	735~765	760-930	760-1410	780-1420
Min. Ground Clearance(mm)		205	205	230	260	241
Min. use weight(kg)		295	300	336	405	465
Gear		(3+1)×2	(3+1)×2	(3+1)×2	(3+1)×2	(3+1)×2
Speed(km/h)	Forward	2.40,3.43,6.13; 9.14,13.08,23.35	2.2; 3.15; 5.62; 8.37; 11.99; 21.41	2.53,4.49,7.54; 9.36,16.63,27.89	2.6,4.63,7.78 ; 9.65,17.14,28.76	2.58,3.95,6.17; 7.71,11.81,18.49
	Reverse	1.94; 7.38	1.78; 6.77	1.99; 7.39	2.06; 7.6	1.94; 5.81
Engine	Model	JT12	QLZ195	JTZ195	ZS1100	ZS1110
	Type	Single cylinder; horizontal; 4 stroke; hopper water cooled; diesel				
Rated Power(kw)		7.35	8.1	8.82	11	13.2
Rated Speed(rpm)		2400	2200	2400	2200	2200
Bore ×Stroke (mm)		92×90	95×100	95×98	100×115	110×115
Total Displacement(L)		0.598	0.709	0.694	0.903	0.993
Tyre		6.00-12	6.00-12	6.00-14	6.00-16	6.00-16